






## Features

- ※ UP to 72.5°FOV
- ※ USB 3.0 interface,raw data output
- ※ Support standard UVC prorocol
- ※ With OSD menu,support image flip
- ※ Come with IR remote controller
- ※ Support standard VISCA & Pelco communication protocols
- ※ RS232IN/IR RS232OUT/RS485 control interface,support daisy chain
- ※ Special mechanical PTZ driving system,ensure precise positioning
- ※ Provide an extra DVI-D video interface
- ※ UP to 12X Optacal zoom,12X digital zoom
- ※ UP to 1080p60 HD video format

## Dimensional Drawing



- 1 USB3.0
- 2 DVI-D
- 3 RS-232IN/IR
- 4 RS-232OUT/RS485
- 5 DC12V

## Technical Specification

Model No.	AMC-E200U3	AMC-E210U3
Image Sensor	1/2.8" Exmor CMOS, 2.14MP	
Video Standard(HD)	1920x1080P/60/50/30/25/20/15/10/5 1280x720P/60/50/30/25/20/15/10/5 1024x768P/60/50/30/25/20/15/10/5 800x600P/60/50/30/25/20/15/10/5 640x480P/60/50/30/25/20/15/10/5	
IRIS	F1.6 - F2.8	F1.6 - F3.0
Noise Reduction	2D/3D	
Focal	f = 3.9mm -46.8mm	f=4.7mm-47mm
Zoom	Optical: 12X, Digital: 12X	Optical: 10X
Field of View	72.5° - 6.3°	
Focus	Auto, Manual, PTZ Trigger AF, One push	
Min.Illumination	0.5Lux(Color), 0.1Lux(B/W)	
Shutter Speed	1/1 - 1/10,000s	
AGC	Auto/Manual	
White Balance	Auto, Indoor, Outdoor, One push, Manual, Automatic Tracking,Sodium,Fluorescent	
AE Control	Auto, Manual, Shutter Priority, Iris Priority,Intelligence	
BLC	Yes	
WDR	Yes	
<b>PTZ</b>		
Pan Range	-170° - +170°	
Tilt Range	-30° - +90°	
Pan Speed	0.1° - +120°/s	
Tilt Speed	0.1° - +80°/s	
Preset Number	256	
OSD	Yes	
Image Flip	Yes	
<b>Interface</b>		
Video Output	USB3.0,DVI-D	
Control Interface	USB3.0,RS-232IN/IR, RS-232OUT/RS-485	
<b>General</b>		
Protocol	VISCA and Support Daisy Chain, PELCO-D, PELCO-P	
Spectra Address	0 - 63	
Power Supply	DC12V	
Working Temp	0°C - +40°C	
Storage Temp	-20°C - +60°C	
Dimension	243mm x 145mm x 163mm	
Weight	1.2KG	
Color	Grey	

\*\*\* Product specification are subject to change without notice \*\*\*